



ER655H

SDLG Compact Excavator
5.9 t (13,007 lbs) | 35.5 kW (48 hp)

● Highlights

- The ER655H is equipped with a Yanmar engine designed to work seamlessly with the hydraulic system, providing optimal break out force and lifting capacity.
- Enhanced stability created by a reinforced X frame and an oversized track gauge.
- New generation ROPS&TOP guard providing a comfortable and spacious operating environment, as well as an excellent field of view improving the operating experience.
- Standard unit offers a 12V outlet, USB port, radio, Bluetooth, and hands-free phone.
- Thumb and hydraulic quick coupler are standard offering on this model.
- Auxiliary pipelines with 5 quick connectors, allow attachments to be changed quickly and efficiently.




Reliability In Action

Specifications

Operating weight	kg (lbs)	5,900 (13,007)
Engine model	-	Yanmar 4TNV86CT
Rated power	kW (hp)	35.5 (48)
Rated engine speed	rpm	2,400
Displacement	ml (in³)	2,091 (127.6)
Pump capacity	L/min (gal/min)	151.2 (39.9)
Main relief set pressure	bar (psi)	263 (3814.5)
Travel low speed	km/h (mi/h)	2.2 (1.4)
Travel high speed	km/h (mi/h)	4.4 (2.7)
Gradeability	°	30
Max. digging force of bucket	kN (lbf)	45 (10,116)
Max. digging force of arm	kN (lbf)	27.5 (6,182)
Swing speed	r/min	10
Blade (width * height)	mm (in)	380 (15") * 1,980 (78")
Ground pressure	kPa (psi)	33.4 (4.8)
Fuel tank	L (gal)	65 (17.2)

Dimensions



Boom length	mm (ft in)	2,800 (9' 2")
Arm length	mm (ft in)	1,540 (5' 0.6")
Bucket capacity	m³ (yd³)	0.18 (0.24)
A Max. digging reach	mm (ft in)	6,043 (19' 10")
B Max. digging reach on ground	mm (ft in)	5,910 (19' 5")
C Max. cutting height	mm (ft in)	5,608 (18' 5")
D Max. dumping height	mm (ft in)	3,876 (12' 8")
E Max. digging depth	mm (ft in)	3,492 (11' 5")
F Max. digging depth (horizontal 8 ft)	mm (ft in)	3,090 (10' 2")
G Max. vertical wall digging depth	mm (ft in)	2,633 (8' 8")
H Overall shipping Height	mm (ft in)	2,545 (8' 4")
I Tail swing radius	mm (ft in)	1,090 (3' 7")
J Min. front swing radius	mm (ft in)	2,637 (8' 8")
K Undercarriage Length	mm (ft in)	2,500 (8' 2")
L Overall shipping Length	mm (ft in)	5,485 (18')
M Track width	mm (ft in)	400 (1' 4")
W Overall shipping width	mm (ft in)	1,980 (6' 6")

*SDLG reserves the right to change these specifications at any time without prior notification. If you need more information, please contact your local distributor or SDLG.



Congratulations SDLG for winning EFQM Global Excellence Award, one of the top three quality awards in the world.

Member of the VOLVO Group since 2006

SDLG is member of the Volvo Group and a leading international manufacturer of construction machinery, and the national-level high-tech company, with a wide network of dealerships and service workshops throughout the world.

SDLG Europe Corp.

Website: www.sdlg.com Email: info@sdlg.com